

LION BATTERIES

Conventional Low Maintenance (BLACK)



Lion Part No.	Description	CCA	Amp Hour	RC	Nom. Max Dim (mm)			Weight	Terminal	Battery Assembly	Warranty
		at -18°C	20hr Rate	Mins	L	W	H	Kgs			Months*
AUTOMOTIVE											
227	NS40ZL	320		50	185	125	225	10	B	C	18
228	NS40Z	320		50	185	125	225	10	B	D	18
229	NS40ZAL	320		50	185	125	225	10	D	C	18
231	NS60L	360		60	234	132	230	12	B	C	18
232	NS60	360		60	234	132	230	12	B	D	18
239	N43	320		45	240	135	210	11	G	C	18
241	NS60LS	325		70	235	135	230	11	D	C	18
242	NS60S	325		70	235	135	230	11	D	D	18
250	N50	440		80	238	172	205	14	D	D	18
250EF	N50EF	440		80	238	172	205	14	D	D	18
251	N51	440		80	238	172	215	14	G	C	18
259	55D23L	510		100	232	171	224	19.3	D	C	18
TRUCK AND TRACTOR											
205	12N24-3	250		30	185	125	175	10.2	I	C	18
206	12N24-4	250		30	185	125	175	10.2	I	D	18
225	6 Volt	800		310	300	170	225	23	D	A	18
263	NS70L	580		120	258	170	220	18.4	D	C	18
264	NS70	580		120	258	170	220	18.4	D	D	18
281	N70ZZL	600		135	300	172	225	22	D	C	18
282	N70ZZ	600		135	300	170	225	22	D	D	18
291	N150	870		240	505	220	235	40	D	F	18
292	N120	720		200	500	180	235	30	D	F	18
294	N94	760		250	505	210	205	35	D	E	18
294E	N94 Euro	1200		270	472	209	221	35	D	E	18
295	N200	1000		380	515	270	235	51	D	F	18
EUROPEAN AUTOMOTIVE											
203	6 Volt	280		80	184	167	186	7.5	D	A	18
255	DIN55	470		90	242	175	175	13	D	C	18
257	DIN66	550		110	278	175	175	16.6	D	C	18
283	DIN88	750		170	348	173	175	21.0	D	C	18

*Private use only