

LION BATTERIES

Premium Sealed Maintenance Free (RED)



Lion Part No.	Description	CCA	Amp Hour	RC	Nom. Max Dim (mm)			Weight	Terminal	Battery Assembly	Warranty Months*
		at -18°C	20hr Rate	Mins	L	W	H	Kgs			
SMF PASSENGER											
427	NS40ZL	360		63	185	125	225	11	B	C	30
428	NS40Z	360		63	185	125	225	11	B	D	30
429	NS40ZAL	360		63	185	125	225	11	D	C	30
430	NS40ZA	360		63	185	125	225	11	D	D	30
431	NS60L (Small post)	430		75	235	140	220	12.8	B	C	30
432	NS60 (Small post)	430		75	235	140	220	12.8	B	D	30
433	NS60LS	430		75	235	140	220	12.8	D	C	30
434	NS60S	430		75	235	140	220	12.8	D	D	30
439	N43	320		45	240	135	210	11.5	G	C	30
440	N41	320		45	240	135	210	11.5	D	D	30
450	N50	550		85	240	174	212	15.2	D	D	30
450EF	N50EF	550		85	240	174	212	15.2	D	D	30
451	N51	550		85	240	174	212	15.2	D	C	30
451EB	N51EB	550		85	240	174	212	15.2	G	C	30
452	N50	610		100	240	174	212	15.2	D	D	30
453	N51DF	610		100	240	174	212	15.2	D	C	30
454	Front terminal	550		84	229	179	212	15.2	R	D	30
458	55D23R	600		100	232	171	224	19	D	D	30
459	55D23L	600		100	232	171	224	19	D	C	30
465	50D20L	450		85	202	173	225	15	D	C	30
465B	50D20L Base holdown	450		85	202	173	225	15	D	C	30
466	50D20R	450		85	202	173	225	15	D	D	30
SMF TRUCK & TRACTOR											
405	U1	330		40	190	128	180	8	I	C	30
406	U1R	330		40	190	128	180	8	I	D	30
462	Front terminal	710		110	260	179	205	17.5	R	D	30
463B	NS70L	630		130	258	168	227	17.5	D	C	30
464B	NS70	630		130	258	168	227	17.5	D	D	30
481	N70ZZL	760		160	306	173	226	21.8	D	C	30
482	N70ZZ	760		160	306	173	226	21.8	D	D	30
485	N86	930		180	332	174	243	26	D	CP	30
485T	SMF1000LS (Stud)	930		180	332	174	243	26	C	CP	30
486	N87	830		180	332	174	243	26	D	D	30
487	N86 High crank	1020		205	330	173	240	26.5	D	C	30
490	N100	730		182	405	173	235	28.5	D	D	30
490L	N100L	730		182	405	173	235	28.5	D	C	30
491	N150	1000		300	505	220	235	39	D	F	30
492	N120	900		230	505	183	240	33	D	F	30
492R	N120R	900		230	505	183	240	33	D	E	30
494E	N94 Euro	1100		250	505	210	221	35	D	E	30
495	N200	1200		430	523	279	224	55	D	F	30
65D	65	700		130	292	189	191	20	D	D	30
SMF EUROPEAN DIN											
435	DIN44	340		52	205	172	175	13.8	D	C	30
435T	DIN44 Tall	400		55	205	172	190	14.1	D	C	30
455	DIN55	560		94	243	175	175	12	D	C	30
456	DIN66 Reverse	620		110	278	175	175	14	D	D	30
456T	DIN66 Tall reverse	710		140	278	175	190	14.5	D	D	30
457	DIN66	620		110	278	175	175	14	D	C	30
457T	DIN66 Tall	710		140	277	175	190	16.8	D	C	30
460	DIN55 Tall reverse	540		110	243	175	190	14	D	D	30
461	DIN55 Tall	520		100	243	175	190	14	D	C	30
475	DIN77	740		135	315	175	175	19	D	C	30
475T	DIN77 Tall	810		170	315	175	190	19.5	D	C	30
476T	DIN77 Tall reverse	810		170	315	175	190	19	D	D	30
483	DIN88	820		148	348	175	175	20	D	C	30
483T	DIN88 Tall	850		175	353	175	190	22.5	D	C	30
493T	DIN95 Tall	930		205	393	174	188	27	D	C	30

Lion Part No.	Description	CCA	Amp Hour	RC	Nom. Max Dim (mm)			Weight	Terminal	Battery Assembly	Warranty Months*
		at -18°C	20hr Rate	Mins	L	W	H	Kgs			
SMF EFB PASSENGER											
431 EFB	NS60L	460	55		238	129	227	13	B	C	18
432 EFB	NS60	460	55		238	129	227	13	B	D	18
458 EFB	EFB Q85R	600	65		232	173	225	19	D	D	18
459 EFB	EFB Q85	600	65		232	173	225	19	D	C	18
SMF EFB TRUCK & TRACTOR											
463 EFB	EFB S95	680	70		260	173	225	18	D	C	18
464 EFB	EFB S95R	680	70		260	173	225	18	D	D	18
481 EFB	EFB T110	760	95		306	173	225	22.5	D	C	18
SMF EFB EUROPEAN DIN											
455T EFB	EFB L2	560	60		242	175	190	15	D	C	18
457T EFB	EFB L3	680	70		278	175	190	20.8	D	C	18
AGM EUROPEAN DIN											
455TAGM	AGM60L2 (DIN55)	640	60		242	175	190	17.6	D	C	18
457TAGM	AGM70L3 (DIN66)	760	70		278	175	190	20.6	D	C	18
475TAGM	AGM80L4 (DIN77)	800	80		315	175	190	23	D	C	18
483TAGM	AGM95L5 (DIN 88)	850	95		353	175	190	27.5	D	C	18
493TAGM	AGM105L6 (DIN95)	950	105		393	175	190	30.5	D	C	18
SMF DEEP CYCLE											
SMF DCM 24	DNS70	600	82		258	173	226	18	A	D	12
SMF DCM 24L	DNS70L	600	82		258	173	226	18	A	C	12
SMF DCM 27	D70Z	680	100		305	175	225	23	A	D	12
SMF DCM 27L	D70ZL	680	100		305	175	225	23	A	C	12
SMF DCM 31	D87	800	120		332	174	243	28	A	D	12
SMF DCM 31L	D87L	800	120		332	174	243	28	A	C	12
SMF DCM 150	150AH	870	150		505	220	240	41	D	F	12
SMF DCM 200	D200	1100	200		523	279	248	64	D	F	12
SMF MARINE											
SMFM24-810	NS70M	680		140	258	173	226	17.5	A	D	24
SMFM27-860	NS70ZM	730		160	306	168	227	22	A	D	24
SMFM31-1060	N86M	930		200	332	174	243	29.4	A	D	24
COMMERCIAL DEEP CYCLE											
812	N12D (6 Volt)		105		230	175	225	14	D	A	12
810	T105 (6 Volt)		225		260	180	265	29	J	A	12
830	GC2-125 (6 Volt)		240		260	180	265	30.7	J	A	12
820	GC2-145 (6 Volt)		260		260	180	295	33	J	A	12
CR-275	9C11 (J250H/US-250HC)		275		298	183	286	34.1	J	A	12
CR-330	8C6V (E305) (6 Volt)		330		310	183	359	43.6	J	A	12
CR-430	8L16 (L16) (6 Volt)		430		314	183	410	55.2	J	A	12
CR-215	8C12V		215		394	178	368	59.5	F	A	12
880	GC8-875 (8 Volt)		170		264	181	245	29	J	D	12
870	GC2-1275 (12 Volt)		150		329	181	245	27.6	J	D	12

*Private use only