



## LION BATTERIES

COMMERCIAL DEEP CYCLE SPECIFICATIONS CHART



Lion Part No.	Description	CCA	Amp Hour	Nom. Max Dim (mm)			Weight	Terminal	Battery Assembly	Warranty
		at -18°C	20hr Rate	L	W	H	Kgs			Months*
<b>COMMERCIAL DEEP CYCLE</b>										
812	N12D (6 Volt)		105	230	175	225	14	D	A	12
810	T105 (6 Volt)		225	260	180	265	29	J	A	12
830	GC2-125 (6 Volt)		240	260	180	265	30.7	J	A	12
820	GC2-145 (6 Volt)		260	260	180	295	33	J	A	12
CR-275	9C11 (J250H/US-250HC)		275	298	183	286	34.1	J	A	12
CR-330	8C6V (E305) (6 Volt)		330	310	183	359	43.6	J	A	12
CR-430	8L16 (L16) (6 Volt)		430	314	183	410	55.2	J	A	12
CR-215	8C12V		215	394	178	368	59.5	F	A	12
880	GC8-875 (8 Volt)		170	264	181	245	29	J	D	12
870	GC2-1275 (12 Volt)		150	329	181	245	27.6	J	D	12
<b>AGM (Absorbed Glass Matt) batteries (Commercial)</b>										
HZB12-80		435	80	259	168	208	23	Q	D	12
HZB12-100		490	100	305	168	208	28.4	Q	D	12
<b>Recreational AGM (Absorbed Glass Matt) batteries</b>										
HZB-EV6-160HR		900	200	298	171	226	26.8	Q	A	12
HZB-EV6-180 (6 Volt)		911	200	260	181	246	29.9	Q	A	12
<b>GEL (Gelled Electrolyte) batteries (Heavy Duty Deep Cycle)</b>										
HZY-EV12-26		142	26	168	178	124	8.8	Q	C	12
HZY-EV12-33		172	36	195	130	160	10.2	L	D	12
HZY-EV12-44		220	45	198	167	157	13.5	Q	C	12
HZY-EV12-55		294	59	229	138	213	16.8	L	C	12
HZY-EV12-80		425	87	260	168	211	24	N	D	12
HZY-EV12-100		520	105	306	168	211	28.3	N	D	12
HZY-EV12-150		784	159	482	170	242	45	N	D	12
HZY-EV12-230		940	263	521	269	203	74.5	N	F	12
HZY-EV6-225		850	225	240	180	263	34	Q	A	12