

ROCKET SEALED MAINTENANCE FREE AUTOMOTIVE SPECIFICATIONS CHART



Jan-14

Lion Part No	Description	Voltage	CCA	Amp Hour	RC	Nom. Max Dim (mm)			Wet	Terminal	Battery	Comments
		Volt	at -18°C	20hr Rate	Mins	L	W	H	kgs		Assembly	
AUTOMOTIVE BATTERIES (SEALED MAINTENANCE FREE)												
427	NS40ZL		360		63	185	125	225	11	B	C	
428	NS40Z		360		63	185	125	225	11	B	D	
429	NS40ZAL		360		63	185	125	225	11	D	C	
430	NS40ZA		360		63	185	125	225	11	D	D	
431	SMFNS60L (small post)		430		75	235	140	220	12.8	B	C	
432	SMFNS60R (small post)		430		75	235	140	220	12.8	B	D	
433	SMFNS60LS		430		75	235	140	220	12.8	D	C	
434	SMFNS60S		430		75	235	140	220	12.8	D	D	
450EF/450	N50		550		85	240	174	212	15.2	D	D	
451	N51		550		85	240	174	212	15.2	G	C	
451EB	N51EB		550		85	240	174	212	15.2	G	C	
452	SMF452		610		100	240	174	212	15.2	D	D	
453	SMF453 dual fit post		610		100	240	174	212	15.2	G	C	
454	Front and top terminal		550		84	229	179	212	15.2	R	D	
458	SMF55D23R		550		100	232	171	224	19	D	D	
459	SMF55D23L		550		100	232	171	224	19	D	C	
459B	SMF 453 standard post		550		95	229	174	212	15.2	D	C	
465	50D20L		450		85	202	173	225	15	D	C	
EUROPEAN AUTOMOTIVE BATTERIES (SEALED MAINTENANCE FREE)												
435	DIN44		340		52	205	172	205	13.8	D	C	
435T	DIN44T		400		55	205	172	190	14.1	D	C	
455	SMF55457 (Din 55)		500		94	243	175	175	12	D	C	
456	SMF (Din 66 Reverse)		580		110	278	175	175	14	D	D	
456T	DIN66TR		670		140	278	175	190	14.5	D	D	
457	SMF56318 (Din 66)		580		110	278	175	175	14	D	C	
457T	SMF56638 (Din66 Tall)		580		140	277	175	190	16.8	D	C	
460	DIN55TR		550		110	243	175	175	14	D	D	
461	SMF56219 (Din55 Tall)		550		100	245	175	190	14	D	C	
475	SMF Din 77		780		135	315	175	175	19	D	C	
475T	DIN77T		810		170	315	175	190	19.5	D	C	
476T	Din 77 RT		700		170	315	175	190	19	D	D	
483	SMF58515 (Din 88)		770		148	348	175	175	20	D	C	
483T	(Din 88T)		770		175	353	175	190	22.5	D	C	
493T	(Din 95T)		930		205	393	174	188	27	D	C	
EUROPEAN AGM BATTERIES												
AGM60L2	DIN55		640	60		242	175	190	17.6	D	C	
AGM70L3	DIN66		760	70		278	175	190	20.6	D	C	
AGM80L4	DIN77		800	80		315	175	190	23	D	C	
TRUCK & TRACTOR BATTERIES (SEALED MAINTENANCE FREE)												
405	U1		330		40	190	128	180	8	I	C	
406	U1R		330		40	190	128	180	8	I	D	
462	Front and top terminal		710		110	260	179	205	17.5	R	D	
463B	SMFNS70L		630		130	258	168	227	17.5	D	C	
464B	SMFNS70		630		130	258	168	227	17.5	D	D	
65D	US Battery		700		130	292	189	191	20	D	D	
481	SMF70ZL		760		160	306	173	226	21.8	D	C	
482	SMF70Z		760		160	306	173	226	21.8	D	D	
485	SMF1000LA		930		180	332	174	243	26	D	CP*	
485T	SMF1000LS (Stud)		930		180	332	174	243	26	C	CP*	
486	SMF86		830		180	332	174	243	26	D	D	
487	High crank 485		1020		205	330	173	240	26.5	D	C	
490	N100		730		182	405	173	235	28.5	D	D	
490L	N100R		730		182	405	173	235	28.5	D	C	
491	SMFN150		1000		300	505	220	235	39	D	F	
492	SMFN120		820		230	505	183	240	33	D	F	
492R	N120R		820		230	505	183	240	33	E	F	
495	SMFN200		1200		430	523	279	224	55	D	F	

Lion Batteries
 1300 782 786
www.lionbatteries.com.au