

# DURACELL MAINTENANCE FREE AUTOMOTIVE SPECIFICATIONS CHART

Jan-13

Duracell Part No	Voltage	CCA	Amp Hour	RC	Nom. Max Dim (mm)			Wet	Terminal	Battery
	Volt	at -18°C	20hr Rate	Mins	L	W	H	kgs		Assembly
<b>AUTOMOTIVE AGM BATTERIES</b>										
AGMUIP	12	320	32	45	197	130	184	11.36	Y/Z	D
AGM35	12	680	50	100	248	175	197	17.69	D	C
AGM47	12	600	60	100	242	175	190	17.69	D	C
AGM48	12	760	70	120	278	175	190	20.64	D	C
AGM49	12	850	92	170	354	175	190	26.54	D	C
AGM94R	12	800	80	140	315	175	190	23.36	D	C
AGM78DT	12	775	55	120	273	175	203	19.28	D	D/T
AGM78	12	775	55	120	273	175	184	19.28	D	S/T
AGM34	12	775	55	120	273	175	203	18.60	D	C
AGM34R	12	775	55	120	273	175	203	18.60	D	D
<b>AGM DUAL PURPOSE BATTERIES (ABSORBED GLASS MAT)</b>										
AGM24DC	12	525	79	135	276	171	251	24.04	U	D
AGM34M	12	775	55	120	273	175	212	18.82	U	D
AGM27DC	12	580	92	324	324	171	221	28.58	U	D
AGM31DC	12	800	105	200	329	171	238	31.30	U	D
AGM4D	12	1110	198	380	527	216	254	58.51	D	F
AGM8D	12	1450	245	480	527	279	254	111.13	D	F
AGMG2	12	680	190	380	260	181	276	31.75	U	A

[www.DDABatteries.com.au](http://www.DDABatteries.com.au)