



Series	AGM-S	Warranty	See Warranty Terms
Volts	6	BCI	GC2
Cells	3		
Terminal Type	M8 incl. TP08		
Included Hardware	M8 stainless bolts & washers & TP08 adapter		
Size & Thread	M8		

Charge

Charge Voltage Range	2.45 V/cell @ 25°C (77°F)
Float Voltage Range	2.3 V/cell @ 25°C (77°F)
Recommended Charge Current	45 A
Maximum Charge Current	65 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	1.3 mΩ

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	740			
Reserve Capacity (RC @ 25A)	431 Minutes			
Reserve Capacity (RC @ 75A)	113 Minutes			
Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	245 AH	2.45 A
@ 20 Hour Rate	220 AH	11.0 A
@ 10 Hour Rate	205 AH	20.5 A
@ 5 Hour Rate	175 AH	35.0 A

Cut Off Voltage	Constant Current Discharge						
	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr
VPC	120.6	72.7	52.2	41.5	34.9	24.8	21.1


Specifications

	Weight	29 kg	64 lbs
	Length	26.0 cm	10.2 "
	Width	18.0 cm	7.09 "
	Height Inc. Term.	26.4 cm	10.4 "


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Nylon Strap


Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



Detailed Illustration



Rev.#2 | August 2022

